

Diesel System Super Clean

Revision date: 28.11.2022

Product code: 2507

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Diesel System Super Clean

UFI: 2H6W-SJXS-SX43-7UXD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent for Diesel Systems

1.3. Details of the supplier of the safety data sheet

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

1.4. Emergency telephone number: GBK GmbH: +49-(0)6132-84463 (24/7)

Further Information

Article Number: 1241, 1242, 1243, 1245, 1246, 1247, 1248, 1249

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 3; H226
Acute Tox. 4; H332
Asp. Tox. 1; H304
Skin Irrit. 2; H315
Eye Irrit. 2; H319
STOT SE 3; H335
STOT RE 2; H373
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics
2-ethyl-hexanol
xylene
2-Ethyl hexyl nitrate

Signal word: Danger

Pictograms:



Hazard statements

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.

Diesel System Super Clean

Revision date: 28.11.2022

Product code: 2507

Page 2 of 14

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves and eye/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P312	Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P501	Dispose of this material and its container to hazardous or special waste collection point.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H304-H332-H335-H373-H412

Precautionary statements

P101-P102-P260-P271-P301+P310-P331-P312-P405-P501

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Surface tension compounds
Detergents, Dispersants
Synthetic agent combinations
corrosion preventing agent
Multifunction Diesel Fuel Additive

Diesel System Super Clean

Revision date: 28.11.2022

Product code: 2507

Page 3 of 14

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-48-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics			60 - < 65 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
104-76-7	2-ethyl-hexanol			10 - < 15 %
	203-234-3		01-2119487289-20	
	Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H332 H315 H319 H335			
1330-20-7	xylene			10 - < 15 %
	215-535-7		01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412			
27247-96-7	2-Ethyl hexyl nitrate			5 - < 10 %
	248-363-6		01-2119539586-27	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Aquatic Chronic 2; H332 H312 H302 H411 EUH044 EUH066			
70024-69-0	Benzenesulfonic acid, mono-C16-24- alkyl derivs., calcium salts			1 - < 5 %
	274-263-7		01-2119492616-28	
128-39-2	Reaction mass of 2,6-di-tert-butylphenol and 2,4,6-tri-tert-butylphenol			< 1 %
	907-745-9		01-2119538013-51	
	Eye Dam. 1, Aquatic Chronic 1; H318 H410			
108-88-3	toluene			< 1 %
	203-625-9		01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H336 H373 H304 H412			
69011-36-5	isotridecanole, ethoxylised			< 1 %
	931-138-8			
	Acute Tox. 4, Eye Dam. 1; H302 H318			
121158-58-5	Phenol, dodecyl-, branched			< 0.1 %
	310-154-3		01-2119513207-49	
	Repr. 1B, Skin Corr. 1C, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H360F H314 H318 H400 H410			

Full text of H and EUH statements: see section 16.

Diesel System Super Clean

Revision date: 28.11.2022

Product code: 2507

Page 4 of 14

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-48-9	918-481-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics	60 - < 65 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
104-76-7	203-234-3	2-ethyl-hexanol	10 - < 15 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = >3000 mg/kg; oral: LD50 = 2047 mg/kg	
1330-20-7	215-535-7	xylene	10 - < 15 %
		inhalation: LC50 = 21,7 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 3200 mg/kg; oral: LD50 = 4300 mg/kg	
27247-96-7	248-363-6	2-Ethyl hexyl nitrate	5 - < 10 %
		inhalation: LC50 = 4,6 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = >4820 mg/kg; oral: LD50 = >9640 mg/kg	
70024-69-0	274-263-7	Benzenesulfonic acid, mono-C16-24- alkyl derivs., calcium salts	1 - < 5 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	
108-88-3	203-625-9	toluene	< 1 %
		inhalation: LC50 = 49 mg/l (vapours); dermal: LD50 = 12200 mg/kg	
69011-36-5	931-138-8	isotridecanole, ethoxylised	< 1 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg Eye Dam. 1; H318: >= 10,1 - 100 Eye Irrit. 2; H319: >= 1 - < 10,1	
121158-58-5	310-154-3	Phenol, dodecyl-, branched	< 0.1 %
		M acute; H400: M=10 M chron.; H410: M=10	

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes .
Subsequently wash off with: Water and soap.

After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult physician.

After ingestion

Let water be drunken in little sips (dilution effect). Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.
Irritation of eyes: Irritant effect possible.
After ingestion: Harmful: may cause lung damage if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Warning about danger of aspiration.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder.
Sand.
Carbon dioxide (CO2).

Diesel System Super Clean

Revision date: 28.11.2022

Product code: 2507

Page 5 of 14

alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Formation of decomposition products possible.

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire.

Beat down gas/vapours/mist with water spray.

Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear a self-contained breathing apparatus and chemical resistant suit.

Keep away from sources of ignition - No smoking.

6.2. Environmental precautions

Beat down gas/vapours/mist with water spray.

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Prevent spread over a wide area (e.g. by containment or oil barriers).

6.4. Reference to other sections

No data

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

The substance should only be handled in closed apparatus or systems. Vapours / aerosols must be extracted by suction immediately at point of origin.

Avoid contact with skin and eyes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Advice on general occupational hygiene

Take off immediately all contaminated clothing

Do not breathe gas/fumes/vapour/spray.

Avoid contact with skin and eyes.

Keep away from food, drink and animal feeding stuffs.

When using do not eat, drink or smoke.

Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

Diesel System Super Clean

Revision date: 28.11.2022

Product code: 2507

Page 6 of 14

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
104-76-7	2-ethylhexan-1-ol	1	5.4		TWA (8 h)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

8.2. Exposure controls

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes. (EN 166)

Hand protection

Tested protective gloves are to be worn: NBR (Nitrile rubber). FKM (Fluoroelastomer (Viton)). (EN374)

Skin protection

Wear suitable solvent-proof protective clothing according to EN 465.

Respiratory protection

In case of accumulation of fumes/aerosols, provide adequate ventilation.

In case of fire: Wear self-contained breathing apparatus.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	yellow, transparent
Odour:	aromatic

Changes in the physical state

Boiling point or initial boiling point and boiling range: 200 - 210 °C

Flash point: 54,5 °C

Lower explosion limits: > 0,6 vol. %

Upper explosion limits: > 7,0 vol. %

Auto-ignition temperature: > 200 °C

Water solubility: insoluble
(at 20 °C)

Solubility in other solvents

Organic solvents

Diesel System Super Clean

Revision date: 28.11.2022

Product code: 2507

Page 7 of 14

Vapour pressure: > 8 hPa
(at 20 °C)

Density (at 20 °C): 0,821 g/cm³

9.2. Other information

Other safety characteristics

No data

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

No decomposition when used as intended.

10.5. Incompatible materials

Oxidizing agents.

acid, concentrated.

Alkalis (alkalis), concentrated.

10.6. Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Harmful if inhaled.

ATEmix calculated

ATE (oral) 7874,6 mg/kg; ATE (dermal) 5569,8 mg/kg; ATE (inhalation vapour) 33,12 mg/l; ATE (inhalation dust/mist) 4,516 mg/l

Diesel System Super Clean

Revision date: 28.11.2022

Product code: 2507

Page 8 of 14

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
104-76-7	2-ethyl-hexanol				
	oral	LD50 2047 mg/kg	Rat		
	dermal	LD50 >3000 mg/kg	Rat		
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
1330-20-7	xylene				
	oral	LD50 4300 mg/kg	Rat		
	dermal	LD50 3200 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 21,7 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
27247-96-7	2-Ethyl hexyl nitrate				
	oral	LD50 >9640 mg/kg	Rat		
	dermal	LD50 >4820 mg/kg	Rabbit		
	inhalation (1 h) vapour	LC50 4,6 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
70024-69-0	Benzenesulfonic acid, mono-C16-24- alkyl derivs., calcium salts				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
108-88-3	toluene				
	dermal	LD50 12200 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 49 mg/l	Rat	GESTIS	
69011-36-5	isotridecanole, ethoxylised				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Diesel System Super Clean

Revision date: 28.11.2022

Product code: 2507

Page 9 of 14

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (xylene)

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Other information

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Diesel System Super Clean

Revision date: 28.11.2022

Product code: 2507

Page 10 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics					
	Acute fish toxicity	LC50 1000 mg/l	96 h	Oncorhynchus mykiss		
	Acute algae toxicity	ErC50 1000 mg/l	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 1000 mg/l	48 h	Daphnia magna (Big water flea)		
104-76-7	2-ethyl-hexanol					
	Acute fish toxicity	LC50 17,1 mg/l	96 h	Leuciscus idus		
	Acute algae toxicity	ErC50 11,5 mg/l	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 39 mg/l	48 h	Daphnia magna		
1330-20-7	xylene					
	Acute fish toxicity	LC50 26,7 mg/l	96 h	Pimephales promelas		
27247-96-7	2-Ethyl hexyl nitrate					
	Acute fish toxicity	LC50 2 mg/l	96 h	Fish		
	Acute algae toxicity	ErC50 1-10 mg/l	72 h	Algae		
	Acute crustacea toxicity	EC50 >10 mg/l	48 h	Daphnia magna		
70024-69-0	Benzenesulfonic acid, mono-C16-24- alkyl derivs., calcium salts					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Fish		
	Acute algae toxicity	ErC50 >1000 mg/l	72 h	Algae		
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna		
108-88-3	toluene					
	Acute fish toxicity	LC50 13 mg/l	96 h	Carassius auratus	IUCLID	
	Acute algae toxicity	ErC50 12,5 mg/l	72 h		GESTIS	
69011-36-5	isotridecanole, ethoxylised					
	Acute fish toxicity	LC50 1-10 mg/l	96 h	Cyprinus carpio (Carp)		
	Acute algae toxicity	ErC50 1-10 mg/l	72 h	Fish		
	Acute crustacea toxicity	EC50 1-10 mg/l	48 h	Daphnia magna		

12.2. Persistence and degradability

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
69011-36-5	isotridecanole, ethoxylised			
	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C	> 60 %	28	
	OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A	> 70 %	28	

12.3. Bioaccumulative potential

Diesel System Super Clean

Revision date: 28.11.2022

Product code: 2507

Page 11 of 14

Swims on the water.

Low potential of bio-accumulation.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not dispose with household waste.

Do not allow to enter into surface water or drains.

Arrange about the exact waste code with the local waste disposal expert.

Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Contaminated packaging

Container must be completely emptied.

Do not pierce, cut up or weld unclean container. (Explosion hazard.)

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. xylene
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3



Classification code:	F1
Special Provisions:	274 601
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

Diesel System Super Clean

Revision date: 28.11.2022

Product code: 2507

Page 12 of 14

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.
xylene
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Special Provisions: 274 601
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.
xylene
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Marine pollutant: -
Special Provisions: 223, 274, 955
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.
xylene
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1
IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Diesel System Super Clean

Revision date: 28.11.2022

Product code: 2507

Page 13 of 14

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):

Phenol, dodecyl-, branched

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 30, Entry 40, Entry 48

2010/75/EU (VOC): 96,933 % (795,816 g/l)

2004/42/EC (VOC): 96,933 % (795,816 g/l)

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

Contains: (Regulation (EC) No. 648/2004 [Detergents regulation])

> 30 % aliphatic hydrocarbons

5 - 15 % aromatic hydrocarbons

< 5 % nonionic tensides

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

Additional information

Regarding the EU-directive 2008/105/EU contains the product none of the listed substances.

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics

2-ethyl-hexanol

xylene

2-Ethyl hexyl nitrate

Benzenesulfonic acid, mono-C16-24- alkyl derivs., calcium salts

Reaction mass of 2,6-di-tert-butylphenol and 2,4,6-tri-tert-butylphenol

toluene

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,9,11,12,14,15.

Diesel System Super Clean

Revision date: 28.11.2022

Product code: 2507

Page 14 of 14

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Acute Tox. 4; H332	Calculation method
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H360F	May damage fertility.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH044	Risk of explosion if heated under confinement.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)